IMLURE SERIES | ILLUMINATED MIRROR

FEATURES

- Comes with SMD 2835, 120 led/meter high brightness led chips for highest illumination
- Featuring a smooth & polished edge and brilliant inner frame of frosted light
- Comes with in-buit de-fogger
- Entire assembly meets UL/cUL standards
- Fast lead time and energy efficient LED lighting

CONSTRUCTION

- Copper-free, environmental friendly and corrosion-resistant silvered glass
- Easy to install mirror
- Comes with in-built de-fogger
- Diamond clear glass
- Chassis should be mounted to wall studs; mounting holes are provided

ELECTRICAL

- Accommodates at 120-277VAC at 50/60Hz
- Fixture should be controlled by an external on/off switch
- 0-10V dimming option available on request, dimmable upto 10%
- 120V-277V hardwire electrical connection; provide 36" external wire

LIGHT SOURCE

- Mirror shall have uniform light output in frosted areas, using replaceable LEDs
- Light engine's available in 3000K, 4000K, 5000K and 6500K
- LEDs provides 604 lumens per foot
- Long life luminaires, calculated L70 50,000-hour LED lifespan
- High efficacy LEDs, maximum 100LPW
- Superior color rendering index more than 90+

PRODUCT IMAGE



APPLICATIONS

Residential, Hospitality, Retail

WARRANTY

3-Year limited warranty. Please refer www.highlineled.com/ for complete warranty terms and conditions

LISTINGS

- **UL** Listed
- **Damp Location Rated**











ORDERING INFORMATION

EXAMPLE ORDERING NUMBER: IMLURE-ND-UNV-62-3636-30-80-D

Family	Dimming	Input	Power/Lumens	Size	CCT	CRI	Options
IMLURE	D - Dimming	120 - 120V	62 - 62W, 6200LM	3636 - 36"W x 36"H x 1.75"D	30 - 3000K	80 - 80 CRI	Blank - Not required
	ND - Non-Dimming	277 - 277V	73 - 73W, 7300LM	4836 - 48"W x 36"H x 1.75"D	40 - 4000K	90 - 90 CRI	D - De-fogger
		UNV - Universal			50 - 5000K		T - Touch Switch
					65 - 6500K		NL - Night Light
					l		l



IMLURE SERIES | ILLUMINATED MIRROR

Job Name:

DIMENSIONS



