

IMLURE SERIES | ILLUMINATED MIRROR

Job Name:

FEATURES

- Comes with SMD 2835, 120 led/meter high brightness led chips for highest illumination
- Featuring a smooth & polished edge and brilliant inner frame of frosted light
- Comes with in-buit de-fogger
- Entire assembly meets UL/cUL standards
- Fast lead time and energy efficient LED lighting

CONSTRUCTION

- Copper-free, environmental friendly and corrosion-resistant silvered glass
- Easy to install mirror
- Comes with in-built de-fogger
- Diamond clear glass
- Chassis should be mounted to wall studs; mounting holes are provided

ELECTRICAL

- Accommodates at 120V AC at 50/60Hz
- Fixture should be controlled by an external on/off switch
- 0-10V dimming option available on request (Dimmable upto 10%)
- 120V hardwire electrical connection; provide 36" external wire

LIGHT SOURCE

- Mirror shall have uniform light output in frosted areas, using replaceable LEDs
- Light engine's available in 3000K, 4000K, 5000K and 6500K
- LEDs provides 604 lumens per foot
- Long life luminaires, calculated L70 50,000-hour LED lifespan
- High efficacy LEDs, maximum 100LPW
- Superior color rendering index more than 90+

PRODUCT IMAGE



APPLICATIONS

Residential, Hospitality, Retail

WARRANTY

3-Year limited warranty. Please refer www.highlineled.com/ for complete warranty terms and conditions

LISTINGS

- **UL** Listed
- **Damp Location Rated**









ORDERING INFORMATION

EXAMPLE ORDERING NUMBER: IMLURE-ND-UNV-62-3636-30-80-D

| Family | Dimming | Input | Power/Lumens | Size | ССТ | CRI | Options |
|--------|--------------------|------------------------|-------------------------|------------------------------------|-------------------|--------------------|-------------------------|
| IMLURE | D - Dimming | 120 - 120V | 50 - 50W, 5000LM | 2436 - 24"W x 36"H x 1.75"D | 30 - 3000K | 80 - 80 CRI | Blank - Not required |
| | ND - Non-Dimming | 277 - 277V | 62 - 62W, 6200LM | 3636 - 36"W x 36"H x 1.75"D | 40 - 4000K | 90 - 90 CRI | D - De-fogger |
| | | UNV - Universal | 73 - 73W, 7300LM | 4836 - 48"W x 36"H x 1.75"D | 50 - 5000K | | T - Touch Switch |
| | | | , | | 65 - 6500K | | NL - Night Light |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |
| | | | | | | | |



IMLURE SERIES | ILLUMINATED MIRROR

Job Name:

DIMENSIONS





