# HIGHLINE

# **SFAPL SERIES | SURFACE PANEL LIGHTS**

#### **FEATURES**

- Available in round and square forms with anodized satin nickel finish
- Available wattage range: 15 watts to 30 watts
- Low profile surface mounting luminaire with a modern look & high performance
- · Edge-lit technology creates uniform distribution
- · Low glare optic provides smooth diffused light

#### CONSTRUCTION

- Super Slim Thin Die-cast aluminum frame for low to medium heights ceilings
- · Constructed from durable aluminum that provides thermal cooling
- Aluminum backplate with integral snap tabs
- · Can be mounted in retrofits, new construction, and remodel applications
- Available in round or square configurations

#### **ELECTRICAL**

- Accommodates 120VAC at 50/60Hz
- Comes with UL listed control gear
- Power factor more than 0.9
- Total Harmonic Distortion less than 20%
- Operating temperature: 0° to 120°F (-18°C to 49°C)

#### **LIGHT SOURCE**

- Edge-lit technology uses a reflective light guide panel that disperses light through a diffused lens making it a practical and economical solution with high performance
- · Low glare optic provides smooth diffused light
- Light engine's available in 3000K, 4000K, 5000K and 6500K
- High efficacy up to 100LPW
- Superior color rendering index, more than 80+

#### **PRODUCT IMAGE**



#### **APPLICATIONS**

· Residential, Hospitality, Retail, Office

#### WARRANTY

 3-Year limited warranty. Please refer www.highlineled.com/ for complete warranty terms and conditions

#### **LISTINGS**

- UL Listed Control Gear
- Damp Location Rated







### **ORDERING INFORMATION**

EXAMPLE ORDERING NUMBER: SFAPL-RD-10-ND-120-15-30-80-WH

Family	Shape	Size	Dimming	Input	Power/Lumens	ССТ	CRI	Finish
SFAPL	RD - Round	<b>10</b> - 10.62"	<b>D</b> - Dimming	<b>120</b> - 120V	<b>15 -</b> 15W, 1500LM	<b>30</b> - 3000K	80 - 80 CRI	SN - Satin Nickel
			ND - Non-Dimming	<b>277</b> - 277V	<b>22</b> - 22W, 2200LM	<b>40</b> - 4000K	<b>90</b> - 90 CRI	
				<b>UNV</b> - Universal	<b>30</b> - 30W, 3000LM	<b>50</b> - 5000K		
						<b>65</b> - 6500K		
	<b>SQ</b> - Square	<b>10</b> - 10.62"x10.62"			<b>15</b> - 15W, 1500LM			
					22 - 22W, 2200LM			
					<b>30</b> - 30W, 3000LM			



# SFPL SERIES | SURFACE PANEL LIGHTS

Job Name:

# **DIMENSIONS**



