Job Name:

# EM2400 SERIES | EMERGENCY LIGHT

#### **FEATURES**

- For use with dual voltage 120/277VAC
- Provide 90 minutes of emergency power in the case of power loss
- Fully adjustable lamp head contains 2 x 4Pcs LED configuration
- Brown-out, short-circuit and voltage surge protection
- 90 minute emergency run time, 24 hour recharge time

## CONSTRUCTION

- Injection-molded, flame-retardant, high-impact, thermoplastic housing with snap-fit design components with LED lamps for easy installation
- Universal J-box pattern (j-box not included)
- Track and swivel arrangement permits full range of lamp adjustment, surf mount with top and side knockout for conduit
- Available in two different finish: White and Black

#### **ELECTRICAL**

- Dual voltage input 120V or 277V AC, 60hz
- Emergency unit provided with test switch, status indicator and rechargeable battery.
- Maintenance-free 3.6V nickel-cadmium battery provides 90 minutes of emergency power
- Comes with Brown-out, short-circuit and voltage surge protection
- UL Listed 90 minutes emergency run time

## **LIGHT SOURCE**

- . Each fully adjustable lamp head contains 2 X 4Pcs LED configuration
- High-brightness LEDs, with years free of maintenance free use
- Glare-free LED lamp heads for glare safe ingress

# **APPLICATIONS**

**PRODUCT IMAGE** 

Stairways and hallways

## WARRANTY

• 5-Year limited warranty. Please refer www.highlineled.com/ for complete warranty terms and conditions.

RoHS Z Compliant

## LISTINGS

- UL and cULus Listed
- Meets UL 924, NFPA 101, NEC, FCC Title 47 7, Part 15, Subpart B and OSHA illumination standards
- **Damp Location Rated**

# **ORDERING INFORMATION**

#### EXAMPLE ORDERING NUMBER : EM2200-ND-UNV-WH



